

| GTB P510 PREMIUM | |
|-------------------------|-----------------------------|
| Product Category | Digital printing media |
| Kind of product | Banner |
| Description | Coated Frontlit, Matt, 510g |

| | Unit of measure | Medium Value | Methods - notes |
|----------------------------|---|---|---------------------------|
| Fabric | | 1000Dx1000D 100% PES | DIN EN ISO2060 |
| Structure | Weaving / inch | 20x20 | DIN60001 |
| Total weight | g/m ² | 510±10 | DIN53352 BS3424 Metodo5A |
| PVC weight | g/m ² | 335±5 | DIN53352 BS3424 Metodo5B |
| Fabric weight | g/m ² | 175±5 | DIN53352 BS3424 Metodo5B |
| Standard heights | mm | 1100 – 1370 1600 – 2100 2500 – 3200 | / |
| Standard lenght | m | 50 | / |
| Break resistance | N/5cm | Warp: 2200 Weft: 1900 | DIN53354 BS3424 Metodo6A |
| Tear resistance | N | Warp: 300 Weft: 250 | DIN53356 BS3424 Metodo7B |
| Superficial tension | N/5cm | 60 | DIN53357 BS3425 Metodo9B |
| Heat resistance | C° | - 20 / +70 | DIN53357 BS3425 Metodo10B |
| Properties | <ul style="list-style-type: none"> - Ultra soft, tear-resistant, high-quality - Product with excellent printing performance and high durability | | |
| Fire resistance | Available in B1 version | | |
| REACH references | Cadmium free product, compliance EN71 – 3 | | |
| Ink compatibility | Eco-solvent, Solvent, UV, Latex | | |

The above mentioned datas represent average values obtained from internal tests carried out on samples. They represents the best of our knowledge and they do not constitute a warranty. Because of the many operating conditions, we recommend that the user checks the suitability for the purpose intended for every application, assuming the responsibilities arising from improper use.